

SILICONE APPLICATION *

BASIC DESIGNS	WIDTHS (mm)	THICKNESS (±0,1 mm)	Nº OF LEVELS
Line	1, 2	0,5; 0,8	1 to 3
Wave	1, 2	0,5; 0,8	1 to 3
Stripe	4, 6, 8, 10, 12, 16, 20	0,5; 0,8; 1; 2	1 to 3
Dot	1, 2, 3	0,5; 0,8; 1; 2	1 to 3

COMPOSITION: 100% SILICONE



“We recommend the validation of these conditions on the final product”

PRODUCT USE: Anti-slide characteristics or fashion look detail for technical or fantasy use.
 The main application in our field is on textile ribbons, rigid or elastic.
 The silicone is applied over different types of supports and substrates.
 The composition of the substrates can be of natural, artificial or synthetic fibres and elastomers.
 We always recommend to make the necessary tests to guarantee the final use of the product.
 Upon request, we can test specific characteristics of the product.

SPECIALITES: Possible to add some metallic effects using glitters.

FINISHES: The finishes are made on the supports and always before silicone application.
 The silicone application does not change the characteristics of the support.

COLOURS: The basic colour is transparent. There are available colours for minimum quantites, please consult.

DESIGNS:

-BASIC

- Nº of levels: from 1 to 3 levels on the width of the support!
- Distance between levels: 2 mm to 40 mm.

BASIC DESIGNS	1 st level	2 nd level	3 rd level
Lines			
Waves			
Stripes			
Dots			

FANTASY DESIGNS

Possible to combine designs, only between lines or waves and dots on each level. Develop your own design!

DOTS/ LINES	WAVES/ DOTS

PRESENTATION:



* These specifications are the mostly used and common on our production. Others may be possible upon consult.