PRINTED LABELS SPECIFICATIONS*								
PRINTING SYTEM	DESCRIPTION	MAIN CHARACTERISTICS		DIMENSIONS IN (mm)				
		SUPPORTS	COLOURS VIVACITY	WIDTH		LENGTH		MAX № OF COLOURS
				MIN.	MAX.	MIN.	MAX.	
Heliotextil	Roll to roll. Direct print, rotogravure.	Satin and taffeta fabrics, (coated and normal), woven ribbons. Acetate, polyester, cotton, others.	Very good over light and medium ground colours. Medium on darker colours.		150		250	
Aristocrate	Roll to roll. Direct print, silk screen.		Very good over all coloured grounds.		180		450	
			Very good over all coloured grounds.		500		250	
Offset							214	
					700		1000	
Letterpress	Roll to roll. Direct print, plates.				200		250	
Flexo					250		400	
Thermo		Satin and taffeta fabrics, (coated and normal), woven ribbons, paper Acetate, polyester, cotton, others.					120	
Flock					100		450	
Sublimation			Very good, with 4 colour process possibility.		100		400	
High - frequency	Plain/ sheets. Direct print, welding plates.				100		100	
Rubber relief					100		100	

COMPOSITION: Varies according to each support and printing method.

PRODUCT USE: We always recomend to make the necessary tests to guarantee the final use of the product. Upon request, we can test specific characteristics of the product.

SPECIALITES: Relief print in "velour" or methalic, hot embossing, sublimation, etc..

Each speciality must be confirmed according to the product.

FINISHES: Hardness finishes, fire retardant, aromatic, laminations, etc...

Each finishes must be confirmed according to the product

COLOURS: On the supports there are available catalogues. On the printing colours we can reproduce almost all PMS colours.

MAKE UP-TYPES OF CUT AND FOLD:



 $^{\circ}$ These specifications are the mostly used and commom on our production, others may be possible upon consult.

