

Technical Specifications

Quality	SUB SD		
Main Characteristics	<ul style="list-style-type: none"> • Digital Printed Paper • Best solution for photographic or half tone images • Competitive solution for small runs 		
Presentation (Support)	Paper in rolls or by piece.	Dimensions	Width (mm): 10 up to 1600 Length: up to 5 meters
Colours	Reproduction to PANTONE® colours.		
Indicated Bases	100% Polyester or mainly Polyester composition.		
Washing Instructions			

Recommendations

Recommended Use	<ul style="list-style-type: none"> • Sports outfits • Football equipments 	<ul style="list-style-type: none"> • Cycling • Underwear 	<ul style="list-style-type: none"> • Promotional items • Etc.
Application Conditions	<ul style="list-style-type: none"> • Temperature: 190-210°C • Time: 20-30 sec. • Pressure: 4-6 Bar • The transfer reaches its maximal resistance 36 hours after its application. 		
Storage	<ul style="list-style-type: none"> • Stock in a dry place, without dust and preferably with controlled temperature. • Do not expose to direct solar light or other heat sources. • Do not stack with weight. • In normal conditions recommended durability to apply a transfer is one year from its production. 		
Tests	<ul style="list-style-type: none"> • It is recommended to perform tests over the materials to be used. • HELIOTEXTIL is available to perform tests. 		
Responsibility	<ul style="list-style-type: none"> • HELIOTEXTIL recommends application conditions and will not take any responsibility for the transfer application by the client. • HELIOTEXTIL assumes that before formulating the order and before using the products, the client validated the requirements of intended end use. 		
Presentation	<ul style="list-style-type: none"> • Boxes 	<ul style="list-style-type: none"> • Plastic Bags 	

Application Sequency

